

USAGE - INSTRUCTION

HOW TO USE CARGO GUARD-2000



**CARGO GUARD
2000**

1. Container inspection

Check whether the container is damaged, whether there is a hole or crack on the container wall, the top and bottom. Container doors can be closed tightly and the seal must be good. The container must be dry and clean before loading.

2. Humidity Inspection of container wood floor

Do not use containers with wood floor humidity over 20%, it would increase the risk of damp. Or you need to increase the dosage of desiccant. You may test the humidity with our Timber Humidity Tester.

3. Seal all air-vents on the container wall. Very Important!

Desiccant plays an effective role only in a closed environment. If the container door is not shut tightly, or there is damage on the container or the air-vents inside are not sealed, desiccant will never be able to absorb up the moisture that continually enters from outside.

4. Inspect PE bags and cartons to ensure that there is no damage during transportation

If PE bags being damaged, do not use the product, as it has possibly been exposed to moisture.

5. Hang Dry Strip and recommended dosage

Open the package and hang Dry Strip up to the iron hoop on the container wall, as shown in the picture. **Use 10pcs per 20' container, 20pcs per 40' container, use 22pcs per 40' high container.** For professional advice of desiccant dosage, please contact Topsorb.

6. Put 2 strips in the space close to the container doors

7. Close container doors

8. Storage

Avoid rain and damp, being stored in dry and shady places. For remained desiccant, please tie or seal PE bags and the package, waiting for the next use.



TOPSORB TECHNOLOGY CO., LTD

Add: No.3293, South Hong Mei Rd, Minhang Dist, Shanghai 201108, China.

Tel: 0086-21-34625284 Fax: 0086-21-34625293

Email: info@desiccant.com.cn

Website: www.desiccant.com.cn